

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/014153 A1

(51) International Patent Classification⁷: **B01F 7/28**, 7/00,
15/06, B01J 19/18, 10/02

(74) Agent: **IRNIGER, Ernst**; Troesch Scheidegger Werner
AG, Schwäntemos 14, CH-8126 Zumikon (CH).

(21) International Application Number:
PCT/CH2004/000494

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 6 August 2004 (06.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03018073.1 8 August 2003 (08.08.2003) EP
03019330.4 27 August 2003 (27.08.2003) EP

(81) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **ETH ZÜRICH** [CH/CH]; ETH transfer, Rämistrasse 101, CH-8092 Zürich (CH).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **MORBIDELLI**, Massimo [IT/CH]; Obsthaldenstrasse 63, CH-8046 Zürich (CH). **SOOS**, Miroslav [SK/CH]; Stiglenstrasse 37, CH-8052 Zürich (CH). **WU, Hua** [CN/CH]; Oerlikonerstrasse 56 B, CH-8057 Zürich (CH).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ROTATING STIRRING DEVICE WITH SUBSTANTIALLY NARROW DISTRIBUTION OF ENERGY DISSIPATION RATE



(57) Abstract: A rotating stirring device for generating substantially narrow distribution of energy dissipation rate and avoiding presence of Taylor vortices is disclosed. The device comprises an outer member (1) such as a cylinder with cross-section of circular shape and an inner member (2) with cross-section of equilateral or inequilateral polygon shape with curved cusps. The inner member is preferably concentrically placed within the outer cylinder and rotates. Such device is particularly advantageous as a reactor or mixer for processes where chemical and physical properties are sensitive to the variations in the shear rate and for processes that involve fragile components. The device can be also used to replace Taylor Couette device for the purposes of improving mass transfer and of avoiding separation of components in the gap in the case of presence of differences in density among components.